

Safety Data Sheet According to Regulation (EC) No. 453/2010

**Revision date:** 

20/05/2014

Version: 1.1

Supersedes:

13/12/2012

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Product form	: Mixture
Trade name	: eni Rotra Bike MG (SAE 85W-140)
EC index no	: N/A
EC no	: N/A
CAS No	: N/A
REACH registration No	: N/A
Product code	: 1322
Formula	: 0081-2012
Product group	: Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses	
Intended for general public	
Main use category	: Industrial use, Professional use, Consumer use
Industrial/Professional use spec	: Wide dispersive use Used in closed systems
Use of the substance/mixture	<ul> <li>Gearbox lubricant</li> <li>Do not use the product for any purposes that have not been advised by the manufacturer. In that case, the user could be exposed to unpredictable risks.</li> </ul>
Function or use category	: Lubricants and additives

#### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

ENI S.p.A. P.le E. Mattei 1 - 00144 ROMA Italy Tel (+39) 06 59821 www.eni.com

Contact: Refining & Marketing Division Via Laurentina 449 00142 ROMA Italy Tel (+39) 06 59881 Fax (+39) 06 59885700

Competent person responsible for the Safety Data Sheet (Reg. EC nr. 1907/2006): qualt-t@eni.com

Safety Data Sheet According to Regulation (EC) No. 453/2010 Product code:

1322

Revision date: 20/05/2014

Version: 1.1

### 1.4. Emergency telephone number

: CNIT +39 0382 24444 (24h) (IT + EN)

Poison centre (UK): National Poisons Information Service Edinburgh (24h) (+44) 844 892 0111 0870 600 6266 (UK only) (Source: UN-WHO)

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

#### Classification according to Directive 67/548/EEC or 1999/45/EC

Not classified

#### Adverse physicochemical, human health and environmental effects

Prolonged and repeated skin contact may cause reddening, irritation and dermatitis. For specific information about the toxicological/ecotoxicological properties and classification of this product, see Sect. 11 and/or Sect. 12.

#### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH phrases	: EUH208 - Contains Polysulfides, di-tert-Butyl, Reaction products of 4-methyl-2- pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl. May produce an allergic reaction EUH210 - Safety data sheet available on request
Other:	

General advice

: "Use suitable gloves when handling product. Dispose of used/leftover product and package properly. Protect the environment."

#### 2.3. Other hazards (not relevant for classification)

Physical/chemical	: This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels.
Health	: If the product is handled or used at high temperature, contact with hot product or vapours may cause burns., Any material in case of accidents involving pressurized circuits and the like, may be accidentally injected under the skin, even without external damage. In such a case, the victim should be brought to an hospital as soon as possible, to get specialized medical treatment.
Environment	: None.
Contaminants	: In exceptional cases (i.e prolunged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S.,See Heading 16

Product code:

1322

Revision date: 20/05/2014

Version: 1.1

Safety Data Sheet According to Regulation (EC) No. 453/2010

This substance/mixture does not meet the PBT criteria of REACH, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH, annex XIII.

### SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

3.2.	Mixture	
Comp	osition/information on ingredients	: Mineral base oil, severely refined Additives
		All the mineral base oils contained in this product have a value < 3 $\%$ wt of DMSO extract, according to IP 346/92 (Nota L - Dir. 94/69/CE - Reg (CE) 1272/2008)
Hazar	dous ingredients and/or with	: See table

relevant occupational exposure limits

Name	Product identifier	%	Classification according to Directive 67/548/EEC
Mineral base oil, severely refined (Component)		50 - 74,9	Not classified
Polysulfides, di-tert-Butyl (Additive)	(CAS No) N/D (EC no) Polymer (EC index no) N/D (REACH-no) 01-2119540515-43	3 - 4,99	R43 R53
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl (Additive)	(CAS No) N/A (EC no) 931-384-6 (EC index no) N/D (REACH-no) 01-2119493620-38	0,49 - 1,99	Xn; R22 Xi; R41 R43 N; R51/53
Mineral base oil, severely refined (Additive)		0,49 - 1,99	Not classified
O,O,O-triphenyl phosphorothioate (Additive)	(CAS No) 597-82-0 (EC no) 209-909-9 (EC index no) N/D (REACH-no) N/D	0,001 - 0,49	Repr. Cat.3; R62 Repr. Cat.3; R63 R53
1,3,4-Thiadiazolidine-2,5-dithione, reaction products with hydrogen peroxide and tert-nonanethiol (Additive)	(CAS No) 91648-65-6 (EC no) 293-927-7 (EC index no) N/A (REACH-no) 01-2119976351-35	0,001 - 0,49	Xi; R38 R52/53

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Mineral base oil, severely refined (Component)		50 - 74,9	Not classified
Polysulfides, di-tert-Butyl (Additive)	(CAS No) N/D (EC no) Polymer (EC index no) N/D (REACH-no) 01-2119540515-43	3 - 4,99	Skin Sens. 1B, H317 Aquatic Chronic 4, H413

Safety Data Sheet According to Regulation (EC) No. 453/2010

\_

Product code:

1322

### **Revision date: 20/05/2014**

### Version: 1.1

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl (Additive)	(CAS No) N/A (EC no) 931-384-6 (EC index no) N/D (REACH-no) 01-2119493620-38	0,49 - 1,99	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Mineral base oil, severely refined (Additive)		0,49 - 1,99	Asp. Tox. 1, H304
O,O,O-triphenyl phosphorothioate (Additive)	(CAS No) 597-82-0 (EC no) 209-909-9 (EC index no) N/D (REACH-no) N/D	0,001 - 0,49	Repr. 2, H361 Aquatic Chronic 4, H413
1,3,4-Thiadiazolidine-2,5-dithione, reaction products with hydrogen peroxide and tert-nonanethiol (Additive)	(CAS No) 91648-65-6 (EC no) 293-927-7 (EC index no) N/A (REACH-no) 01-2119976351-35	0,001 - 0,49	Aquatic Chronic 3, H412

Full text of R-, H- and EUH-phrases: see section 16

### **SECTION 4: First aid measures**

4.1. Description of first aid measu	res
First-aid measures general	: In case of spontaneous vomiting, transport the victim to a hospital, to verify the possibility that the product has been aspired into the lungs.
First-aid measures after inhalation	: In case of disturbances owing to inhalation of vapours or mists, remove the victim from exposure; keep at rest; if necessary, seek medical attention. See also Point 4.3.
First-aid measures after skin contact	: Take off contaminated clothing and shoes. Wash thoroughly with soap and water. If inflammation or irritation persists, seek medical advice. In case of contact with hot product, cool affected part with plenty of cold water, and cover with gauze or clean cloth. Call a doctor or bring to an hospital. Do not use salves or ointments, unless directed by doctor. Do not put ice on the burn.
First-aid measures after eye contact	: Rinse eyes thoroughly for at least 15 minutes. Keep eyelids well apart. If irritation persists, seek medical advice. In case of contact with hot product, cool affected part with plenty of cold water, and cover with gauze or clean cloth. Call a doctor or bring to an hospital. Do not use salves or ointments, unless directed by doctor.
First-aid measures after ingestion	: Do not induce vomiting to avoid aspiration into the lungs. If the person is conscious, rinse mouth with water without swallowing. Keep at rest. Call for medical assistance or bring to an hospital. If the casualty is inconscious, place in the recovery position. In case of spontaneous vomiting, keep head low, to avoid the risk of aspiration into the lungs. Do not give anything by mouth to an unconscious person.
4.2. Most important symptoms an	d effects, both acute and delayed
Symptoms / injuries (general indications)	: Prolonged and repeated skin contact may cause reddening, irritation and dermatitis.
Symptoms/injuries after inhalation	: This product has a low vapour pressure, and in normal conditions at ambient temperature the concentration in the air is negligible. A significant concentration may build up only if the product is used at high temperature, or in case of sprays and mists. In these cases overexposure to vapours may cause irritation to airways, nausea and dizziness.
Symptoms/injuries after skin contact	: Prolonged and repeated skin contact may cause reddening, irritation and dermatitis, due to a defatting effect. Contact with hot product may cause thermal burns.

Chronic symptoms

Product code:

1322

Safety Data Sheet According to Regulation (EC) No. 453/2010	Revision date: 20/05/2014
	Version: 1.1
Symptoms/injuries after eye contact	: Contact with eyes may cause a light transient irritation. Contact with hot product or vapours may cause burns.
Symptoms/injuries after ingestion	: Accidental ingestion of small quantities of the product may cause irritation, nausea and gastric disturbances. Taking into account the taste of the product, however, ingestion of dangerous quantites is very unlikely.
Symptoms/injuries upon intravenous administration	: No information available.

: None to be reported, according to our present knowledge.

4.3. Indication of any immediate medical attention and special treatment needed

If there is any suspicion of inhalation of H2S (hydrogen sulphide). The casualty should be sent immediately to hospital. Immediately begin artificial respiration if breathing has ceased. Administer oxygen if necessary. Seek medical attention in all cases of serious burns.

SECTION 5: Firefighting measures			
5.1. Extinguishing media			
Suitable extinguishing media	: Small-size fires: carbon dioxide, dry chemicals, foam, sand or earth. Large fires: foam or water fog (mist). These means should be used by trained personnel only. Other extinguishing gases (according to regulations).		
Unsuitable extinguishing media	: Do not use water jets. They could cause splattering, and spread the fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.		
5.2. Special hazards arising from th	e substance or mixture		
Fire hazard	: This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels.		
Explosion hazard	: In case of losses from pressurized circuits, the sprays may form mists. Take into account that in this case the lower explosion limit for mists is about 45 g/m <sup>3</sup> of air.		
Combustion products	: Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, NOx, H2S and SOx,Oxygenated compounds (aldehydes, etc.),POx.		
5.3. Advice for firefighters			
Firefighting instructions	: Shut off source of product, if possible. If possible, move containers and drums away from danger area. Spilled product which is not burning should be covered with sand or foam. Use water sprays to cool containers and surfaces exposed to the flames. If the fire cannot be controlled, evacuate area.		
Special protective equipment for firefighters	: Personal protection equipment for firefighters (see also sect. 8). Self-contained breathing apparatus.		
Other information	: In case of fire, do not discharge residual product, waste materials and runoff water: collect separately and use a proper treatment.		

### SECTION 6: Accidental release measures

6.1.	Personal precautions, protective equipment and emergency procedures	
Genera	l measures	: Stop or contain leak at the source, if safe to do so. Eliminate all ignition sources if safe to do so (e.g. electricity, sparks, fires, flares). Avoid accidental sprays on hot surfaces or electrical contacts. Avoid direct contact with released material. Keep upwind.
6.1.1.	For non-emergency personnel	

Safety Data Sheet

According to Regulation (EC) No. 453/2010

1322

**Revision date: 20/05/2014** 

Version: 1.1

Emergency procedures	: Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency.
6.1.2. For emergency responders	
Protective equipment	: Small spillages: normal antistatic working clothes are usually adequate. Large spillages: full body suit of chemically resistant and antistatic material. if necessary heat resistant and insulated. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Gloves made of PVA are not water-resistant, and are not suitable for emergency use. If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated. Work helmet. Antistatic non-skid safety shoes or boots. Goggles and /or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory protection: A half or full-face respirator with filter(s) for organic vapours (and when applicable for H2S). A Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
Emergency procedures	: Notify local authorities according to relevant regulations.

### 6.2. Environmental precautions

Do not let the product accumulate in confined or underground spaces. Do not let the product flow into sewers or water courses, or in any way contaminate the environment. In case of contamination of environment compartments (soil, subsoil, surface or underground waters), remove contaminated soil when possible, and in any case treat all involved compartments in accordance with local regulations.

6.3. Methods and material for cont	Methods and material for containment and cleaning up	
For containment	: Soil. Contain spilled liquid with sand, earth or other suitable absorbents (non- flammable). Recover free liquid and waste materials in suitable waterproof and oil- resistant containers. Clean contaminated area. Dispose of according to local regulations. Water: Confine the spillage. Remove from surface by skimming or suitable floating absorbents. Collect recovered product and other waste materials in suitable waterproof, oil resistant containers. Recover or dispose of according to loca regulations. Do not use solvents or dispersants, unless specifically advised by an expert, and, if required, approved by local authorities.	
Other information	: Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air/water temperature, wave/current direction and speed) may significantly influence the choice of appropriate actions. Local regulations may also prescribe or limit actions to be taken. For this reason, local experts should be consulted when necessary.	

### 6.4. Reference to other sections

Refer to chapter 16.

Product code:

Safety Data Sheet

According to Regulation (EC) No. 453/2010

SECTION 7: Handling and storage

Revision date: 20/05/2014

1322

Version: 1.1

7.1. Precautions for safe han	dling
Precautions for safe handling	: Ensure that all relevant regulations regarding handling and storage facilities of flammable products are followed. Do not use compressed air for filling, discharging, or handling operations. Keep away from heat/sparks/open flames/hot surfaces. Use and store only outdoors or in a well-ventilated area. During transfer and mixing operations, ensure that all equipment is correctly grounded. Avoid the build-up of electric charges. Emptied containers can contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been drained and cleaned. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content, flammability, and the presence of sulphy compounds. See also Section 16, "Other information".
Handling temperature	: 0 - 55 °C
Hygiene measures	: Avoid contact with skin. Do not breathe fume/ mist/ vapours. Do not ingest. Do not smoke. Do not eat and do not drink during use. Do not clean hands with dirty or oil soaked rags. Do not re-use clothes, if they are still contaminated. Keep away from food and beverages.
7.2. Conditions for safe stora	ge, including any incompatibilities
Storage conditions	: Store in dry, well ventilated area. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke.
Incompatible products	: Keep away from: strong oxidants.
Storage temperature	: 0 - 55 °C
Storage area	: Storage area layout, tank design, equipment and operating procedures must compl with the relevant European, national or local legislation. Storage installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations.
Packages and containers:	: If the product is supplied in containers: Keep containers tightly closed and properly labelled. Keep only in the original container or in a suitable container for this kind o product. Empty containers may contain combustible product residues. Do not weld, solder, drill, cut or incinerate empty containers, unless they have been properly cleaned.
Packaging materials	: For containers, or container linings use materials specifically approved for use with this product. Recommended materials for containers, or container linings use mild steel, stainless steel. Some synthetic materials may be unsuitable for containers or container linings depending on the material specification and intended use. Compatibility should be checked with the manufacturer.

### 7.3. Specific end use(s)

No information available.

### SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Mineral base oil, severely refined		
Austria	MAK (mg/m³)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)

Safety Data Sheet According to Regulation (EC) No. 453/2010 Product code:

1322

Revision date: 20/05/2014

Version: 1.1

Mineral base oil, severely refined		
Belgium	Limit value (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
Italy - Portugal - USA ACGIH	ACGIH TLV®-TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
Italy - Portugal - USA ACGIH	ACGIH TLV®-STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
USA NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
Spain	VLA-ED (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
Spain	VLA-EC (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
The Netherlands	MAC TGG 8h (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
Denmark	Grænseværdi (langvarig) (mg/m³)	1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
Denmark	Grænseværdi (kortvarig) (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
Hungary	AK-érték	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
Sweden	Nivågränsvärde (NVG) (mg/m3)	1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
Sweden	Kortidsvärde (KTV) (mg/m3)	3 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
Canada (Quebec)	VECD (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
Canada (Quebec)	VEMP (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)

Mineral base oil, severely refined		
Austria	MAK (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
Belgium	Limit value (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
Italy - Portugal - USA ACGIH	ACGIH TLV®-TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
Italy - Portugal - USA ACGIH	ACGIH TLV®-STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)

Safety Data Sheet According to Regulation (EC) No. 453/2010 Product code:

1322

Revision date: 20/05/2014

Version: 1.1

Mineral base oil, severely refined		
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
USA NIOSH	NIOSH REL (STEL) (mg/m³)	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
Spain	VLA-ED (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
Spain	VLA-EC (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
The Netherlands	MAC TGG 8h (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
United Kingdom	WEL TWA (mg/m³)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
Denmark	Grænseværdi (langvarig) (mg/m³)	1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
Denmark	Grænseværdi (kortvarig) (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
Hungary	AK-érték	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
Sweden	Nivågränsvärde (NVG) (mg/m3)	1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
Sweden	Kortidsvärde (KTV) (mg/m3)	3 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
Canada (Quebec)	VECD (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)
Canada (Quebec)	VEMP (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO <3% m/m)

: Monitoring procedures should be chosen according to the indications set by national Monitoring methods authorities or labour contracts., Refer to relevant legislation and in any case to the good practice of industrial hygiene. Additional information : Note: The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute shortterm exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

Safety Data Sheet According to Regulation (EC) No. 453/2010

Product code:

1322

Revision date: 20/05/2014

Version: 1.1

8.2. Exposure controls	
Appropriate engineering controls	: Before entering storage tanks and commencing any operation in a confined area, carry out an adequate clean-up, and check the atmosphere for oxygen content, flammability, and the presence of sulphur compounds. See also Section 16, "Other information".
Personal protective equipment (for industrial or professional use)	: Face shield. Gloves. Protective clothing. Safety glasses. Safety shoes or boots. Dust/aerosol mask.
Hand protection	: When there is a risk of contact with the skin, use hydrocarbon-resistant, felt-lined gloves. Use gloves respecting all the conditions and within the limits set by the manufacturer. Replace gloves immediately in case of cuts, holes or other signs of damages or degradation. If necessary, refer to the EN 374 standard. Materials that are presumably adequate: nitrile (NBR) or PVC with a protection index > 5 (permeation time > 240 mins).
Eye protection	: When there is a risk of contact with the eyes, use safety goggles or other means of protection (face shield). If necessary, refer to national standards or to the EN 166 standard.
Skin and body protection	: Long-sleeved overalls. If necessary, refer to the EN 340 and related standards, for definition of characteristics and perfomance according to the risk rating of the area. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated.
Respiratory protection	: Independently from other possible actions (technical modifications, operating procedures, and other means to limit the exposure of workers), personal protection equipment can be used according to necessity. Open or well ventilated spaces: in presence of oil mists and if the product is handled without adequate containment means: use full or half-face masks with filter for mists/aerosols. In case there is a significant presence of vapours (e.g. through handling at high temperature), use ful or half-face masks with filter for hydrocarbon vapours. (EN 136/140/145). Closed o confined areas (e.g. tank interiors): the use of protection measures for airways (masks or self-contained breathing apparatus), must be assessed according to the specific activity, as well as level and duration of predicted exposure. (EN 136/140/145).
Thermal hazard protection	: If contact with hot product is possible or anticipated, gloves should be heat-resistan and thermally insulated.
Environmental exposure controls	: Do not discharge the product into the environment. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.
Consumer exposure controls	: No special requirements necessary, if handled at room temperature.
8.3. Hygiene measures	
General protective and hygienic measures	S : Avoid contact with skin and eyes, Do not breathe vapours or mists., Do not clean hands with dirty or oil-soaked rags., Do not keep dirty rags in the overall pockets., D not drink, eat or smoke with dirty hands., Wash hands with water and mild soap, do not use solvents or other irritant products which have a defatting effect on the skin., Do not re-use clothes, if they are still contaminated.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

: Liquid

Physical state

Product code:

1322

Revision date: 20/05/2014

Safety Data Sheet According to Regulation (EC) No. 453/2010

Version: 1.1

Appearance	: Liquid, bright & clear.
Molecular mass	: Not applicable for mixtures
Colour	: Yellow to amber.
Odour	: Slight odour of petroleum.
Odour threshold	: There are no data available on the preparation/mixture itself.
рН	: Not applicable
Relative evaporation rate (butylacetate=1)	: Negligible.
Melting point	: Pour point $\leq$ -27 °C (ASTM D 97)
Freezing point	: No data available
Boiling point	: ≥ 200 °C (ASTM D 1160)
Flash point	: ≥ 175 °C (ASTM D 93)
Self ignition temperature	: ≥ 300 °C (DIN 51794)
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: ≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: ≤ 915 kg/m³ (15 °C) (ASTM D 4052)
Solubility	: Water: Immiscible and insoluble
Log Pow	: Not applicable for mixtures
Log Kow	: No data available
Viscosity, kinematic	: 27,5 mm²/s (100 °C) (ASTM D 445)
Viscosity, dynamic	: No data available
Explosive properties	: None.
Oxidising properties	: None.
Explosive limits	: LEL $\geq$ 45 g/m <sup>3</sup> (Mineral oil mists)
9.2. Other information	
VOC content	: = 0 % (EU, CH)

The above data are typical values and do not constitute a specification.

Safety Data Sheet

According to Regulation (EC) No. 453/2010

Product code:

Revision date: 20/05/2014

1322

Version: 1.1

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

This mixture does not offer any further hazard for reactivity, except what is reported in the following paragraphs.

#### **10.2.** Chemical stability

Stable product, according to its intrinsic properties (in normal conditions of storage and handling).

#### 10.3. Possibility of hazardous reactions

None (in normal conditions of storage and handling). Contact with strong oxidizers (peroxides, chromates, etc.) may cause a fire hazard. A mixture with nitrates or other strong oxidisers (e.g. chlorates, perchlorates, liquid oxygen) may create an explosive mass. Sensitivity to heat, friction or shock cannot be assessed in advance.

### **10.4.** Conditions to avoid

Keep away from strong oxidizers. Keep away from open flames, hot surfaces and sources of ignition. Avoid the build-up of electrostatic charge.

### **10.5.** Incompatible materials

Strong oxidants.

### **10.6.** Hazardous decomposition products

None.

### SECTION 11: Toxicological information

11.1. Information on tox	cicological effects
Acute toxicity	: Not classified (Based on available data, the classification criteria are not met) (according to composition)
eni Rotra Bike MG (SAE 8	5W-140) (N/A)
LD50 oral rat	$\geq$ 2000 mg/kg bodyweight (Calculated data). This evaluation is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.

	· ··· F · ··· · / · · ·· FF · ·
LD50 dermal rabbit	$\geq$ 2000 mg/kg bodyweight (Calculated data). This evaluation is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.
LC50 inhalation rat (mg/l)	$\geq$ 5 mg/l/4h (Calculated data). This evaluation is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.

Mineral base oil, severely refined	
LD50 oral rat	> 5000 mg/kg bodyweight (OECD 401)
LD50 dermal rat	> 5000 mg/kg bodyweight (OECD 402)
LC50 inhalation rat (mg/l)	> 5 mg/l/4h (OECD 403)

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with	
diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl (N/A)	
ATE (oral)	500,000 mg/kg

Safety Data Sheet According to Regulation (EC) No. 453/2010

Product code:

1322

Revision date: 20/05/2014

Version: 1.1

Mineral base oil, severely refined	≥ 5000 mg/kg bodyweight (OECD 401)
LD50 dermal rat	$\geq$ 5000 mg/kg bodyweight (OECD 402)
LC50 inhalation rat (mg/l)	$\geq 5 \text{ mg/l/4h (OECD 403)}$
Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met)
	(according to composition) Prolonged and repeated skin contact may cause reddening, irritation and dermatit due to a defatting effect.
	pH: Not applicable
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met)
	(according to composition)
	pH: Not applicable
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
	<ul> <li>(according to composition)</li> <li>This product is formulated with a component containing one or more sensitizers.</li> <li>According to information provided by the supplier, test results on a similar formulation show that the finished product does not need to be classified as sensitizing.</li> <li>Therefore the data in Section 3 for the content of sensitizers should not be directl used to classify the product for sensitization.</li> </ul>
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
	(according to composition) This product does not contain any significant amounts of substances classified as mutagenic by the EU (in any case < $0.1$ % wt)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
	(according to composition) None of the components of this product are listed as carcinogen by NTP, IARC, OSHA, EU or others. All the mineral base oils contained in this product have a value < 3 % wt of DMSC extract, according to IP 346/92 (Nota L - Dir. 94/69/CE - Reg (CE) 1272/2008)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
	(according to composition)
Specific target organ toxicity (single exposure)	: Not classified (Based on available data, the classification criteria are not met) (according to composition)
Specific target organ toxicity (repeated exposure)	: Not classified (Based on available data, the classification criteria are not met) (according to composition)

Mineral base oil, severely refined	
LOAEL (oral,rat,90 days)	= 125 mg/kg bodyweight/day (OECD TG 408)

Mineral base oil, severely refined	
LOAEL (oral,rat,90 days)	= 125 mg/kg bodyweight/day (OECD TG 408)

Product code:

1322

Safety Data Sheet According to Regulation (EC) No. 453/2010

Revision date: 20/05/2014

	Version: 1.1
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
	Viscosity, kinematic: > 20,5 mm2/s (40 °C) (ASTM D 445)
Potential Adverse human health effects and symptoms	: Prolonged and repeated skin contact may cause reddening, irritation and dermatitis, due to a defatting effect. Contact with eyes may cause temporary reddening and irritation.
Other information	: None.

12.1. Toxicity	
Ecology - general	: According to the components, and by comparison with other products of the same type and composition, it is expected that this product has a toxicity for aquatic organisms > 100 mg/l, and must not be regarded as dangerous to the environment. An uncontrolled release to the environment may nevertheless produce a contamination of environmental compartments (air). Handle according to general working hygiene practices to avoid pollution and release into the environment.
Ecology - air	: This product has a low vapour pressure. A significant exposure may happen only if the product is used at high temperature, or in case of sprays and mists.
Ecology - water	: This product is not soluble in water. It floats on water and forms a film on the surface. The damage to aquatic organisms is of mechanical kind (immobilization and entrapment)

eni Rotra Bike MG (SAE 85W-140) (N/A)	
LC50 fish 1	$\geq$ 100 mg/l (Calculated data). This evaluation is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.
EC50 Daphnia 1	$\geq$ 100 mg/l (Calculated data). This evaluation is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.
ErC50 (algae)	$\geq$ 100 mg/l (Calculated data). This evaluation is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.

Mineral base oil, severely refined	
LC50 fish 1	> 100 mg/l (LL 50)
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)

Mineral base oil, severely refined	
LC50 fish 1	> 100 mg/l (LL 50)
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)

12.2. Persistence and degradability	
eni Rotra Bike MG (SAE 85W-140) (N/	A)
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.

Safety Data Sheet According to Regulation (EC) No. 453/2010 Product code:

1322

Revision date: 20/05/2014

Version: 1.1

Mineral base oil, severely refined	
Persistence and degradability	The most significant constituents of the product should be considered as
	"inherently biodegradable", but not "readily biodegradable", and they may be
	moderately persistent, particularly in anaerobic conditions.

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl (N/A)	
Biodegradation	3,6 - 7,4 % (28d - OECD 301 B)

Mineral base oil, severely refined	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.

1,3,4-Thiadiazolidine-2,5-dithione, reaction products with hydrogen peroxide and tert-nonanethiol (91648-65-6)	
Biodegradation	2 % (28d; MITI 1)

### 12.3. Bioaccumulative potential

eni Rotra Bike MG (SAE 85W-140) (N/A)	
Log Pow	Not applicable for mixtures

1,3,4-Thiadiazolidine-2,5-dithione, rea	ction products with hydrogen peroxide and tert-nonanethiol (91648-65-6)
Log Kow	9,4 (0.1 d)

### **12.4.** Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment	
eni Rotra Bike MG (SAE 85W-140) (N/A)	
This substance/mixture does not meet the PBT criteria of REACH, annex XIII.	
This substance/mixture does not meet the vPvB criteria of REACH, annex XIII.	
Results of PBT-vPvB assessment	The components in this formulation do not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)

Mineral base oil, severely refined	
This substance/mixture does not meet the PBT criteria of REACH, annex XIII.	
This substance/mixture does not meet the vPvB criteria of REACH, annex XIII.	
Results of PBT-vPvB assessment	This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)

Safety Data Sheet According to Regulation (EC) No. 453/2010

Product code:

1322

Revision date: 20/05/2014

Version: 1.1

Mineral base oil, severely refined	
This substance/mixture does not meet the PBT criteria of REACH, annex XIII.	
This substance/mixture does not meet the vPvB criteria of REACH, annex XIII.	
Results of PBT-vPvB assessment	This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)

12.6. Other adverse effects	
Other adverse effects	: None.
Other information	: This product has no specific properties for inhibition of bacterial activity. In any case, wastewater containing this product should be treated in plants that are suited for the specific purpose.

SECTION 13: Disposal considerations	
<b>13.1.</b> Waste treatment methods	
Waste treatment methods	: Do not dispose of the product, either new or used, by discharging into sewers, tunnels, lakes or water courses. Deliver to a qualified official collector.
Sewage disposal recommendations	Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. Dispose of in a safe manner in accordance with local/national regulations.
Waste disposal recommendations	: European Waste Catalogue code(s) (Decision 2001/118/CE): 13 02 05* (mineral- based non-chlorinated engine, gear and lubricating oils). This EWC code is only a general indication, and takes into account the original composition of the product and its intended use. The user has the responsibility of choosing the right EWC code considering the actual use of the product, alterations and contaminations.
Additional information	Empty containers may contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been cleaned, and declared safe. Dispose of empty, not cleaned containers safely, according to local regulations.
Ecology - waste materials	: The product as it is does not contain halogenated substances.

### SECTION 14: Transport information

In accordance with ADR / RID / ADNR / IMDG / ICAO / IATA

14.1. UN number	
No dangerous good in sense of transport regulations	
14.2. UN proper shipping name	
Proper Shipping Name	: Not applicable
14.3. Transport hazard class(es)	
Subsidiary risk (IMDG)	:
Subsidiary risk (IATA)	:
14.4. Packing group	
Packing group (UN)	:
14.5. Environmental hazards	
Other information	: None.

Safety Data Sheet

According to Regulation (EC) No. 453/2010

Product code:

1322

Revision date: 20/05/2014

Version: 1.1

14.6. Special precautions for user	
Special transport precautions	: None.
14.6.1. Overland transport	
Transport regulations (ADR)	: Not subject
Transport regulations (RID)	: Not subject
Classification code	:
Limited quantities (ADR)	:
14.6.2. Transport by sea	
Transport regulations (IMDG)	: Not subject
Transport regulations (ADNR)	: Not subject
Port Regulation Law	: Not applicable.
Limited quantities (IMDG)	: Not applicable
EmS-No. (1)	:
MFAG-No	:
14.6.3. Air transport	
Transport regulations (IATA)	: Not subject
Instruction "cargo" (ICAO)	: Not applicable
Instruction "passenger" (ICAO)	: Not applicable
Instruction "passenger" - Limited quantities (ICAO)	: Not applicable

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

IBC code

: None.

### **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.1.1. EU-Regulations

No REACH Annex XVII restrictions

No ingredients are included in the REACH Candidate list (> 0,1 % m/m).

Product code:

1322

Revision date: 20/05/2014

Safety Data Sheet According to Regulation (EC) No. 453/2010

Version: 1.1

Relevant EU Legislation	<ul> <li>Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). (et sequens).</li> <li>Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16</li> </ul>
	December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (et sequens).
	Directives 89/391/CEE, 89/654/CEE, 89/655/CEE, 89/656/CEE, 90/269/CEE, 90/270/CEE, 90/394/CEE, 90/679/CEE, 93/88/CEE, 95/63/CE, 97/42/CE, 98/24/CE, 99/38/CE, 99/92/CE, 2001/45/CE, 2003/10/CE, 2003/18/CE (Health and safety on the workplace)
	Directive 98/24/EC (protection of the health and safety of workers from the risks related to chemical agents at work).
	Directive 92/85/CE (measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding)
	Directives 96/82/CE and 2003/105/CE (Control of major-accident hazards involving dangerous substances) Directive 2004/42/CE (Limitation of emissions of Volatile Organic Compounds)
	Labelling according to directives 67/548/EEC and 1999/45/EC
VOC content	: = 0 % (EU, CH)
EURAL code (EWC)	: 13 02 05*
15.1.2. National regulations	
Maladies professionelles (F)	: RG 36 - Affections provoquées par les huiles et graisses d'origine minérale ou de synthèse
Water hazard class (WGK) (D)	: 1 (according to composition)
WGK remark	: Classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS)
Storage class (LGK) (D)	: LGK 12 - Non-flammable liquids in non-flammable packages
VbF class (D)	: Not applicable.
Regional legislation	<ul> <li>National adoption of EU Directives concerning health and safety on the workplace. National laws on classification and labeling of dangerous substances/preparations (Adoption of Directive 67/548/CE and subsequent Adaptations to Technical Progress - ATP, and Directive 1999/45/CE). National adoption of EU Directives concerning control of major-accident hazards involving dangerous substances (96/82/CE - 2003/105/CE). Relevant national laws on prevention of water pollution. Relevant national laws on protection of the health of pregnant workers (National adoption of Dir. 92/85/EEC). National adoption of Directives 75/439/CEE - 87/101/CEE concerning disposal of used oils.</li> </ul>

### 15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out Mineral base oil, severely refined Polysulfides, di-tert-Butyl Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus

pentaoxide, and salted by amines, C12-14- tert-alkyl

Mineral base oil, severely refined

1,3,4-Thiadiazolidine-2,5-dithione, reaction products with hydrogen peroxide and tert-nonanethiol

Safety Data Sheet According to Regulation (EC) No. 453/2010

SECTION 16: Other information

Product code:

Revision date: 20/05/2014

Version: 1.1

Indication of changes	: Formula. Reproductive toxicity.
Data sources	: This Safety Data Sheet is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.
Abbreviations and acronyms	: Complete text of the phrases H and R quoted in this Safety Data Sheet. These phrases are reported here for information only, and MAY NOT correspond to the classification of the product.
	N/A = Not applicable.
	N/D = Not available
	ACGIH = American Conference of Governmental Industrial Hygienists API = American Petroleum Institute
	CSR = Chemical Safety Report
	DNEL = Derived No Effect Level
	DMEL = Derived Minimum Effect Level
	EC50 = Effective Concentration, 50%
	EL50 = Effective Loading, 50 %
	EPA = Environmental Protection Agency
	IC50 = Inhibition Concentration, 50%
	LC50 = Lethal Concentration, 50% LD50 = Lethal Dose, 50%
	LL50 = Lethal Loading, 50%
	LOAEL = Low Observed Adverse Effects Level
	NOEL = No Observed Effects Level
	NOAEL = No Observed Adverse Effects Level
	OECD = Organization for Economic Cooperation and Development
	PNEC = Predicted No-Effect Concentration
	PBT = Persistent, Bioaccumulative, Toxic
	STOT = Single Target Organ Toxicity (STOT) RE = (Single Target Organ Toxicity) Repeated exposure
	(STOT) SE = (Single Target Organ Toxicity) Single exposure
	TLV®TWA = Threshold Limit Value – Time-Weighted Average
	$TLV \otimes STEL = Threshold Limit Value \otimes - Short Term Exposure Limit$
	UVCB = Substance of Unknown or Variable composition, Complex reaction product
	or Biological materials
	vPvB = very Persistent, very Bioaccumulative
	WAF = Water Accommodated Fraction.
Training advice	: Provide adequate training to professional operators for the use of PPEs, according the information contained in this Safety Data Sheet.
Other information	: Do not use the product for any purposes that have not been advised by the manufacturer. In that case, the user could be exposed to unpredictable risks.
	. In exceptional cases (i.e prolunged storage in tanks contaminated with water, an
	presence of anaerobic sulfate-reducing microbial colonies), the product may under
	a degradation and generate small amounts of sulfur compounds, including H2S.
	This situation is especially relevant in all those circumstances which require to enter a confined space, with direct exposure to the vapours. If this possibility is suspected
	a specific assessment of inhalation risks from the presence of H2S in confined
	spaces must be made, to help determine prevention measures and controls (i.e.
	PPE) appropriate to local circumstances, and adequate emergency procedures. If
	there is any suspicion of inhalation of H2S (hydrogen sulphide), Rescuers must we
	breathing apparatus, belt and safety rope, and follow rescue procedures. Send
	patient to hospital. Immediately begin artificial respiration if breathing has ceased.
	Administer oxygen if necessary.

Product code:

Revision date: 20/05/2014

Version: 1.1

Safety Data Sheet According to Regulation (EC) No. 453/2010

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
Repr. 2	Reproductive toxicity, Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
Skin Sens. 1B	Sensitisation — Skin, category 1B
H226	Flammable liquid and vapour
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H361	Suspected of damaging fertility or the unborn child
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects
H413	May cause long lasting harmful effects to aquatic life
R22	Harmful if swallowed
R38	Irritating to skin
R41	Risk of serious damage to eyes
R43	May cause sensitisation by skin contact
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environmen
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environm
R53	May cause long-term adverse effects in the aquatic environment
R62	Possible risk of impaired fertility
R63	Possible risk of harm to the unborn child
Ν	Dangerous for the environment
Xi	Irritant
Xn	Harmful.

SDS EU ( Annex II) GENERAL

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product